

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number
WO 2005/044710 A1

(51) International Patent Classification⁷: **B66B 7/04**, 1/34

TRACEY, Michael [US/US]; 637 Main Street, Cromwell,
CT 06416 (US).

(21) International Application Number:

PCT/US2003/031927

(74) Agent: **GASKEY, David J.**; Carlson, Gaskey & Olds, 400
W. Maple Rd., Ste. 350, Birmingham, MI 48009 (US).

(22) International Filing Date: 8 October 2003 (08.10.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(71) Applicant (for all designated States except US): **OTIS EL-
EVATOR COMPANY** [US/US]; Ten Farm Springs Road,
Farmington, CT 06032 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(72) Inventors; and

(75) Inventors/Applicants (for US only): **KULAK, Richard**
[US/US]; 80 Aldbourne Drive, Bristol, CT 06010 (US).

(54) Title: **ELEVATOR ROLLER GUIDE WITH VARIABLE STIFFNESS DAMPER**



(57) Abstract: An elevator system roller guide device (26) includes a plurality of rollers (32) that roll along a guide rail (28). Dampers (40) that have a selectively variable stiffness dampen lateral movements between the rollers (32) and roller guide device base (30) as the elevator car assembly (20) moves through a hoistway. In one example, the dampers include a magneto-rheological fluid. A controller (50) selectively controls a magnetic field generated by an electromagnet (52) to selectively control the viscosity of the magneto-rheological fluid and the stiffness of the dampers (40).



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

Declaration under Rule 4.17:

— *of inventorship (Rule 4.17(iv)) for US only*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.